

ALUMINIUM LOADING RAMPS

Product Range September 2009



"ATV SERIES"

Suitable for use with lightweight machinery such as ATVs.
Suitable for pneumatic tyres. *Not suitable for steel tracks.*


PRODUCT CODE	RATED CAPACITY	RAMP MASS	RAMP LENGTH	TRACK WIDTH (internal)	RAMP WIDTH	RAMP DEPTH
6/0821ATV	800kg	7kg	2.1m	250mm	290mm	65mm
6/0821ATVF	800kg	8kg	2.1m folding	250mm	290mm	65mm



"MOWER SERIES"

Suitable for use with lightweight machinery such as Ride-on Mowers.
Suitable for pneumatic tyres. *Not suitable for steel tracks.*

PRODUCT CODE	RATED CAPACITY	RAMP MASS	RAMP LENGTH	TRACK WIDTH (internal)	RAMP WIDTH	RAMP DEPTH
6/0621OS	600kg	6kg	2.1m	235mm	275mm	55mm
6/0621OSF	600kg	7kg	2.1m folding	235mm	275mm	55mm



"PNEUMATIC SERIES"

Suitable for pneumatic tyres.
*Not suitable for steel tracks or steel tracks with rubber pads.
Not optimum for rubber tracks. Not suitable for solid tyres.*


PRODUCT CODE	RATED CAPACITY	RAMP MASS	RAMP LENGTH	TRACK WIDTH (internal)	RAMP WIDTH	RAMP DEPTH
6/1033	1000kg	22kg	3.3m	350mm	440mm	90mm
6/1524	1500kg	16kg	2.4m	300mm	390mm	90mm
7/1929	1900kg	18kg	2.9m	300mm	390mm	90mm
7/3029	3000kg	24kg	2.9m	300mm	400mm	110mm
7/3033	3000kg	27kg	3.3m	300mm	400mm	110mm
7/3633	3600kg	31kg	3.3m	350mm	450mm	120mm
7/4040	4000kg	35kg	4.0m	375mm	485mm	125mm
7/4536	4500kg	36kg	3.6m	375mm	485mm	125mm
7/4833	4800kg	33kg	3.3m	375mm	485mm	125mm
7/6036P	6000kg	49kg	3.6m	500mm	620mm	160mm

Custom designs: P.O.A

Continued overleaf...

ALUMINIUM LOADING RAMPS

Product Range September 2009



"TRACK SERIES"

Suitable for steel tracks including steel tracks with rubber pads.
Recommended for rubber tracks. Suitable, but not optimum for rubber tyres.

PRODUCT CODE	RATED CAPACITY	RAMP MASS	RAMP LENGTH	TRACK WIDTH (internal)	RAMP WIDTH	RAMP DEPTH
7/3033T	3000kg	32kg	3.3m	350mm	450mm	110mm
7/3633T	3600kg	37kg	3.3m	400mm	500mm	120mm
7/4040T	4000kg	47kg	4.0m	400mm	510mm	125mm
7/4536T	4500kg	41kg	3.6m	400mm	510mm	125mm
7/4536TW	4500kg	43kg	3.6m	450mm	560mm	125mm
7/4833T	4800kg	37kg	3.3m	400mm	510mm	125mm
7/4833TW	4800kg	39kg	3.3m	450mm	560mm	125mm
7/6036T	6000kg	53kg	3.6m	500mm	620mm	160mm
7/7536T	7500kg	58kg	3.6m	500mm	600mm	184mm
7/9037(T)	9000kg	71kg	3.7m	500mm	640mm	200mm
7/11537(T)	11500kg	85kg	3.7m	500mm	660mm	180mm



"PT SERIES"

Suitable for All Surface Loader rubber tracks. Suitable for pneumatic tyres.
Not suitable for steel tracks or steel tracks with rubber pads.

PRODUCT CODE	RATED CAPACITY	RAMP MASS	RAMP LENGTH	TRACK WIDTH (internal)	RAMP WIDTH	RAMP DEPTH
7/3033PT	3000kg	39kg	3.3m	450mm	550mm	110mm
7/3033PTW	3000kg	41kg	3.3m	500mm	600mm	110mm
7/4536PT	4500kg	44kg	3.6m	500mm	610mm	125mm
7/4536PTW	4500kg	46kg	3.6m	550mm	660mm	125mm
7/6036PT	6000kg	49kg	3.6m	500mm	620mm	160mm

Custom designs: P.O.A